

PartDB

Itemy dodajemy, gdy tylko ma to sens, sztuka po sztuce jako pojedyncze Zapasy.

Etykiety mi — na rastrowe paskowe labelarki

userscript do strony itema, pokazujący się po refreshu, dodający przycisk Copy do każdego Lotu

```
// ==UserScript==
// @name      Knyfyrstel PartDB Lot Formatter
// @namespace  Violentmonkey Scripts
// @match     https://partdb.knyfyrstel.pl/pl/part/*
// @grant     GM_setClipboard
// @version   1.2
// @description Prepare lot string to clipboard from PartDB rows
// ==/UserScript==

(function () {
  'use strict';

  window.addEventListener('load', () => {
    const table = document.querySelector('table');
    if (!table) return;

    table.querySelectorAll('tbody tr').forEach(tr => {
      const btnCell = document.createElement('td');
      const btn = document.createElement('button');
      btn.textContent = '📄 Copy';
      btn.className = 'lot-copy-btn';
      btn.style.padding = '2px 6px';
      btnCell.appendChild(btn);
      tr.appendChild(btnCell);
    });

    table.addEventListener('click', e => {
```

```

if (!e.target.matches('.lot-copy-btn')) return;
const tr = e.target.closest('tr');
try {
  const lotUrl = window.location.href;

  const partName = document.querySelector('[data-bs-original-title="Nazwa"])?.textContent.trim() ||
'NO NAME ??';

  const storageLinks = tr.querySelectorAll('ul.structural_link a');
  const storage = Array.from(storageLinks).map(a => a.textContent.trim()).reverse().join(' < ') || "NO
LOCATION";

  const comment = tr.querySelector('td:first-child)?.textContent.trim();

  const lotIdSpan = Array.from(tr.querySelectorAll('.dropdown-menu span')).find(span =>
  span.textContent.includes('ID:'));
  const lotId = lotIdSpan ? lotIdSpan.textContent.match(/ID:\s*(\d+)/)?.[1] : 'N/A??';

  const partId = window.location.pathname.match(/part\/(\d+)/)?.[1] || 'N/A??';

  // const hasMi = Array.from(tr.querySelectorAll('.tag, .badge, .label')).some(el =>
  // el.textContent.toLowerCase().includes('property of mi')
  // );

  //const mi = hasMi ? '!mi' : '';
  const commentSpan = comment ? ` :: ${comment}` : '';
  const lines = [
    `https://partdb.knyfyr.tel.pl/scan/lot/${lotId}`,
    `${partName}${commentSpan}`,
    `@ ${storage}`,
    `part/${partId} lot/${lotId}`
  ];

  const text = lines.join('\n');
  GM_setClipboard(text);
  alert(`Copied:\n${text}`);
} catch (err) {
  console.error(err);
}

```

```
    alert('Failed to copy lot info. See console for details.');
```

```
  }
```

```
});
```

```
});
```

```
})();
```

Na Brother P-Touch D410 mi drukuje to tak (po dostosowaniu udev i w `nix shell nixpkgs#ptouch-print`):

```
TEMP=`mktemp` && wl-paste > $TEMP && cat $TEMP && head -1 $TEMP |
```

```
  qrtool encode -s 2 -m 1 --symbol-version 4 |
```

```
  ptouch-print --image - --text "`tail -n +2 $TEMP`"
```

Revision #3

Created 24 July 2025 15:05:37 by Mi

Updated 29 March 2026 16:10:01 by Mi